

BY :BORDAR MABNA CO,SA TEHARN-IRAN CEEDUCER PRO™

The portable solution for shallow water hydrographic surveys

Compact

The CEEDUCER PRO™ is a compact fully functional hydrographic survey system, with built in GPS, data logging, a dual channel echosounder and a rechargeable battery. This allows for fast acquisition of bathymetric survey data with minimum fuss.

Rugged

Housed in a rugged Pelican case the CEEDUCER PRO™ is capable of fast deployment in vessels of opportunity and has been designed to be simple to use in the field without impacting data quality.

Dependable

The CEEDUCER PRO™ is currently in use worldwide by defence departments, port & harbour authorities, educational institutes and environmental agencies. It is used in applications ranging from dredging and engineering surveys to beach profiling for environmental studies.

Expandable

The CEEDUCER PRO™ has the ability to accept various external inputs, including: the user's own GPS, RTCM, tide, heave and deep water echosounders. This can extend the CEEDUCER PRO™ survey capabilities.



www.ceehydrosystems.com

TEL: ۸۸۶۶۴۸۱

WWW.BORDARMABNA.COM



BY :BORDAR MABNA CO,SA TEHARN-IRAN

CEEDUCER PRO™

General Specifications

Physical

Dimensions	30.0 x 25.0 x 13.8 cm (L x W x D) 11.81" x 9.84" x 5.43"
Display	320 x 240 backlit graphic LCD with contrast control
Weight	3.7 kg (8.2 lbs)
Colour	Pelican Yellow
Connectors	LEMO 1B & 2B series, Industrial RJ45, TNC

Environmental

Operating temperature	0°C-50°C (32°F-122°F)
Humidity	95% non condensing
Ingress protection rating	IP65

Power

Power consumption	7.2 watts (approx operating time 8 hours) – Crescent
Internal battery	Rechargeable high capacity NiMH battery 10Ah
Antenna voltage output	5.0 VDC
External power supply	Nominal 12.0 VDC @ 2A (9-24 VDC range)

GPS Receiver Options

Hemisphere Crescent L1 (Std)	± 0.6m (95% DGPS)
Hemisphere Eclipse L1/L2 (Opt)	± 0.2m (95% Marinstar HP)
Hemisphere Eclipse L1/L2 (Opt)	± 0.02m (95% RTK)
Timing Output	1 PPS (Pulse Per Second)

IALA Beacon Receiver

Hemisphere SBX-4(Std)	2 channel, parallel tracking
(Crescent GPS receiver only)	Frequency range 283.5-325.0 kHz
	Channel spacing 500 kHz

Echosounder

Depth range	200 kHz 0.3-99.9 m 30 kHz 0.75-99.9 m
Maximum ping rate	6 Hertz
Accuracy	1 cm ± 0.1% of depth
Resolution	1 cm

Transducer Options

Standard 200 kHz	200 kHz, 8° beam width @-3dB
Narrow Beam 200 kHz	200 kHz, 2.7° beam width @-3dB
Dual 200/30 kHz	200/30 kHz, 8°/19° beam width @-3dB

External Data Interfaces

GPS input	NMEA 0183
RTCM input	RTCM v2.3 (DGPS) Crescent & Eclipse RTCM v3.0, ROX, CMR+ (RTK) Eclipse
Heave input	TSS 1
Tide input	CEETIDE
Echosounder	ODOM, NMEA 0183
Baud rate	4800 – 115200
Data bits/parity/stop bits	8/N/1

- Specifications are subject to change
- Visit www.ceehydro.com for the complete list of specifications
- v11299



CEE HydroSystems

Unit 1, 12 Cecil Rd,
Hornsby (Sydney)
NSW 2077
Australia

t: +61 (0) 2 9482 5880
f: +61 (0) 2 9987 1584
e: sales@ceehydro.com
www.ceehydro.com



TEL: ۰۲۹۴۸۲۵۸۸۰ WWW.BORDARMABNA.COM