







BORDAR MABNA CO.SA
SURVEYING, TELECOM & GPS PRODUCTS

تاریخ: ۱۳۹۱/ /

مخاطب آقای:

به شرکت:

ردیف	فهرست کارت LMT، Flexible GSM-BSS Access از شرکت بردار مبنا	تصویر	قیمت ریالی
۱	<p>دستگاه HALCA Adapter (LMT) ساخت کمپانی GPP-NOKIA-SIMENSE Flexible GSM-BSS Access</p> <p>The HDLC and Line Change Adapter HALCA can be used to connect any stationary or mobile PC equipped with a standard parallel interface to a BSS element, TRAU, BTS, or BSC using their T-Interface and the LAPB protocol Dimensions L x W x H = 93 x 56 x 19 mm</p> <p>Interfaces To Computer: Centronics plug for connection to the PS/2-compatible printer interface Power cable with PS/2-USB compatible mouse/keyboard connector</p> <p>To Partner Station: 3m X.21 data cable with 15-pin sub-D connector Power Supply +5V±5%, power consumption max. 200 mA Protocol HDLC (LAPB), X.21, can be configured as DCE or DTE, cycle generated by the DCE. Data Transfer Rate 64 kbit/s Software Interface Via NetBIOS interrupt with NetBIOS control blocks. Memory requirement of driver software approx. 64 Kbytes. Windows 2000/XP Hardware Requirements 80486 processor 33 MHz or better PS/2-compatible printer interface (configured for bidirectional operation)</p>	 <p>اکسترنال مناسب برای استفاده با همه نوع PC</p>  <p>NEW WITH USB POWER IN</p>	<p>قیمت: تماس</p> <p>کد سفارش: ۹۰۱</p>
۲	<p>دستگاه، کارت DLHCIII (LMT) ساخت کمپانی GPP-NOKIA-SIMENSE Flexible GSM-BSS Access</p> <p>Dimensions L x W x H = 85,6 mm x 54 mm x 5 mm</p> <p>Interfaces To PC/Laptop/Notebook: Compatible to PCMCIA Release 2.1, Memory mapped IO To partner station: 2 serial interfaces, optionally X.21 or customized HDLC via IO-connector and Single Link Cable / Double Link Cable Power Supply +5V±5% (via PCMCIA-Interface), power consumption: avg. 150 mA (Single Link with 100 Ohm termination DCE) avg. 220 mA (Double Link with 100 Ohm termination DCE) Protocol HDLC (LAPB/customized HDLC), X.21 Data Transfer Rate 64 kbit/s up to 2.5 Mbit/s Software Interface Socket-based API for WinNT/Win95/Win98 and Win2000/XP. Device node interface for Solaris and Linux . Software Requirements Windows95/98, Solaris 2.6 or Linux Hardware requirements Pentium processor (recommended) PCMCIA-Slot for PC-Card Typ II Available Components DLHC (PCMCIA card) DLHC-SLC (Single Link Cable, 3m) AS A OPTION</p>	 <p>NEW WITH ROHS CERTIFICATE</p> 	<p>قیمت: تماس</p> <p>کد سفارش: ۹۰۲</p>




REF:
LMT-11-01

شرکت بردار مابنا (سهامی خاص)

تجهیزات نقشه برداری، فتوگرامتری، هیدروگرافی، مخابراتی و GPS

نماینده انحصاری **SILVA** SUUNTO در ایران

تهران، پائین تر از میدان ونک، ساختمان اداری ۲۴۱۷، طبقه ۳ شمالی
تلفن: ۷-۸۸۸۷۸۵۰۶ فاکس: ۸۸۷۹۳۴۵۱ WWW.BORDARMABNA.COM

BORDAR MABNA CO.SA SURVEYING TELECOM & GPS تماس	کد سفارش: ۹۰۷		
		<p>کارت مبدل PCMCIA CARD TO 4 USB2 PORTS</p> <p>قابلیت اضافه نمودن ۴ پورت USB از درگاه PCMCIA قابلیت استفاده بعنوان HUB USB2 با توان بالا مناسب برای DRIVE TEST قابل استفاده با TEMS, ...</p>	۷
تماس	کد سفارش: ۹۰۷		